

Huawei CloudEngine S5735-L-V2 Series Switches Datasheet

Huawei CloudEngine S5735-L-V2 series are simplified gigabit Ethernet switches that provide 8/10/16/24/48 x GE downlink ports, 4 x GE or 10GE uplink ports and 2 x 12GE dedicated stack ports

Introduction





CloudEngine S5735-L-V2 series switches are ideal for scenarios such as enterprise campus network access and gigabit to the desktop. Built on next-generation, high-performance hardware and software platform, CloudEngine S5735-L-V2 switches stand out with compelling features such as intelligent stack (iStack), flexible Ethernet networking, and diversified security control. They support multiple Layer 3 routing protocols and provide high performance and service processing capabilities.










Product Overview








Models and Appearances

The following models are available in the CloudEngine S5735-L-V2 series.

Models and appearances of the CloudEngine S5735-L-V2 series

| Models and Appearances | Description |
|---|--|
|  <p>CloudEngine S5735-L8T4S-A-V2</p> | <ul style="list-style-type: none"> 8 x 10/100/1000Base-T ports, 4 x GE SFP ports Built-in AC Forwarding performance: 18 Mpps Switching capacity: 24 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L8P4S-A-V2</p> | <ul style="list-style-type: none"> 8 x 10/100/1000Base-T ports, 4 x GE SFP ports Built-in AC PoE+ Forwarding performance: 18 Mpps Switching capacity: 24 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L10T4X-A-V2</p> | <ul style="list-style-type: none"> 10 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports Built-in AC Forwarding performance: 75 Mpps Switching capacity: 100 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L8P2T4X-A-V2</p> | <ul style="list-style-type: none"> 8 x 10/100/1000Base-T ports(PoE+), 2 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports Built-in AC |

| Models and Appearances | Description |
|--|--|
| | <ul style="list-style-type: none"> Forwarding performance: 75 Mpps Switching capacity: 100 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L10T4X-TA-V2**</p> | <ul style="list-style-type: none"> 10 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports Built-in AC Forwarding performance: 75 Mpps Switching capacity: 100 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L8P2T4X-TA-V2**</p> | <ul style="list-style-type: none"> 8 x 10/100/1000Base-T ports(PoE+), 2 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports Built-in AC Forwarding performance: 75 Mpps Switching capacity: 100 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L16T4S-A-V2</p> | <ul style="list-style-type: none"> 16 x 10/100/1000Base-T ports, 4 x GE SFP ports Built-in AC Forwarding performance: 30 Mpps Switching capacity: 40 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24T4S-A-V2</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x GE SFP ports Built-in AC Forwarding performance: 42 Mpps Switching capacity: 56 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24P4S-A-V2</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x GE SFP ports Built-in AC PoE+ Forwarding performance: 42 Mpps Switching capacity: 56 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24T4XE-A-V2</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 stack ports Built-in AC Forwarding performance: 132 Mpps Switching capacity: 176 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24T4XE-D-V2</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x 10GE SFP+ ports, 2 x 12GE stack ports Built-in DC Forwarding performance: 132 Mpps Switching capacity: 176 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24P4XE-A-V2</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x 10GE SFP+ ports, 2 x 12GE stack ports Built-in AC PoE+ Forwarding performance: 132 Mpps Switching capacity: 176 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L24P4XE-TA-V2**</p> | <ul style="list-style-type: none"> 24 x 10/100/1000Base-T ports, 4 x 10GE SFP+ ports, 2 x 12GE stack ports Built-in AC PoE+ Forwarding performance: 132 Mpps Switching capacity: 176 Gbps/520 Gbps* |

| Models and Appearances | Description |
|--|---|
|  <p>CloudEngine S5735-L48T4S-A-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x GE SFP ports • Built-in AC • Forwarding performance: 78 Mpps • Switching capacity: 104 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48LP4S-A-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x GE SFP ports • Built-in AC • PoE+ • Forwarding performance: 78 Mpps • Switching capacity: 104 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48T4XE-A-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 x12GE stack ports • Built-in AC • Forwarding performance: 168 Mpps • Switching capacity: 224 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48T4XE-TA-V2**</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 x12GE stack ports • Built-in AC • Forwarding performance: 168 Mpps • Switching capacity: 224 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48T4XE-D-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 x12GE stack ports • Built-in DC • Forwarding performance: 168 Mpps • Switching capacity: 224 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48P4XE-A-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 x 12GE stack ports • Built-in AC • PoE+ • Forwarding performance: 168 Mpps • Switching capacity: 224 Gbps/520 Gbps* |
|  <p>CloudEngine S5735-L48LP4XE-A-V2</p> | <ul style="list-style-type: none"> • 48 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports, 2 x12GE stack ports • Built-in AC • PoE+ • Forwarding performance: 168 Mpps • Switching capacity: 224 Gbps/520 Gbps* |


*Note: The value before the slash (/) refers to the device's switching capability, while the value after the slash (/) means the system's switching capability.

**Note: '-T' means Hardware Trust Module(HTM), support hardware root of trust and measurement startup.

Power Supply

Technical specifications of the power supplies applicable to the CloudEngine S5735-L-V2 series

| Power Module | Technical Specifications | Applied Switch Model |
|--------------|--------------------------|----------------------|
|--------------|--------------------------|----------------------|

| Power Module | Technical Specifications | Applied Switch Model |
|--|--|--|
|  PAC1000S56-EB | <ul style="list-style-type: none"> • Dimensions (H x W x D): 40 mm x 66 mm x 215 mm • Weight: 1.1 kg (2.43 lb) • Rated input voltage range: <ul style="list-style-type: none"> – 100 V AC to 130 V AC, 50/60 Hz – 200 V AC to 240 V AC, 50/60 Hz – 240 V DC • Maximum input voltage range: <ul style="list-style-type: none"> – 90 V AC to 290 V AC, 45 Hz to 66 Hz – 190 V DC to 290 V DC • Input current: <ul style="list-style-type: none"> – 100 V AC to 130 V AC: 12 A – 200 V AC to 240 V AC: 8 A – 240 V DC: 8 A • Maximum output current: <ul style="list-style-type: none"> – 100 V AC to 130 V AC input: 12 A – 200 V AC to 240 V AC input and 240 V DC input: 8 A – 240V DC: 8 A • Maximum output power: <ul style="list-style-type: none"> – Total power: 900 W (100 V AC to 130 V AC input)/1000 W (200 V AC to 240 V AC input and 240 V DC input) • Hot swap: Supported | <ul style="list-style-type: none"> • CloudEngine S5735-L48P4XE-A-V2 |

CloudEngine S5735-L48P4XE-A-V2 is a PoE switch. It has one power module slot, which can have a 1000 W PoE power module installed.

The following table lists its power supply configurations.

Power supply configurations of CloudEngine S5735-L48P4XE-A-V2

| Power Module | Available PoE Power | Maximum Number of Ports (Fully Loaded) |
|-----------------------|---------------------|--|
| 1000 W AC PoE (220 V) | 846 W | <ul style="list-style-type: none"> • 802.3af (15.4 W per port): 48 • 802.3at (30 W per port): 28 |
| 1000 W AC PoE (110 V) | 756 W | <ul style="list-style-type: none"> • 802.3af (15.4 W per port): 48 • 802.3at (30 W per port): 25 |

Power supply configurations of CloudEngine S5735-L8P4S-A-V2 & S5735-L8P4X-QA-V2 & S5735-L8P2T4X-A-V2

| Power Module | Available PoE Power | Maximum Number of Ports (Fully Loaded) |
|--------------------------|---------------------|--|
| Built-in AC Power Module | 125 W | <ul style="list-style-type: none"> • 802.3af (15.4 W per port): 8 • 802.3at (30 W per port): 4 |

Power supply configurations of CloudEngine S5735-L24P4S-A-V2 & S5735-L24P4XE-A-V2

| Power Module | Available PoE Power | Maximum Number of Ports (Fully Loaded) |
|--------------|---------------------|--|
|--------------|---------------------|--|

| Power Module | Available PoE Power | Maximum Number of Ports (Fully Loaded) |
|--------------------------|---------------------|--|
| Built-in AC Power Module | 400 W | <ul style="list-style-type: none"> 802.3af (15.4 W per port): 24 802.3at (30 W per port): 13 |

Power supply of CloudEngine S5735-L48LP4S-A-V2 & S5735-L48LP4XE-A-V2

| Power Module | Available PoE Power | Maximum Number of Ports (Fully Loaded) |
|--------------------------|---------------------|--|
| Built-in AC Power Module | 380 W | <ul style="list-style-type: none"> 802.3af (15.4 W per port): 24 802.3at (30 W per port): 12 |

Product Features and Highlights

Flexible Ethernet Networking

- In addition to supporting traditional Spanning Tree Protocol (STP), Rapid Spanning Tree Protocol (RSTP), and Multiple Spanning Tree Protocol (MSTP), CloudEngine S5735-L-V2 is also designed with the industry's latest Ethernet Ring Protection Switching (ERPS) technology. ERPS is defined in ITU-T G.8032, and it implements millisecond-level protection switching based on traditional Ethernet MAC and bridging functions.
- CloudEngine S5735-L-V2 supports Smart Link, which implements backup of uplinks. One CloudEngine S5735-L-V2 switch can connect to multiple aggregation switches through multiple links, significantly improving reliability of access devices.

Diversified Security Control

- CloudEngine S5735-L-V2 supports 802.1X authentication, MAC address authentication, and hybrid authentication on a per port basis, and implements dynamic policy delivery (VLAN, QoS, and ACL) to users.
- CloudEngine S5735-L-V2 provides a series of mechanisms to defend against DoS attacks and user-targeted attacks. DoS attacks are targeted at switches and include SYN flood, Land, Smurf, and ICMP flood attacks. User-targeted attacks include bogus DHCP server attacks, IP/MAC address spoofing, DHCP request flood, and changing of the DHCP CHADDR value.
- CloudEngine S5735-L-V2 sets up and maintains a DHCP snooping binding table, and discards the packets that do not match the table entries. The DHCP snooping trusted port feature ensures that users connect only to the authorized DHCP server.
- CloudEngine S5735-L-V2 supports strict ARP learning. This feature prevents ARP spoofing attackers from exhausting ARP entries so that users can connect to the Internet normally.

Easy Operation and Maintenance

- CloudEngine S5735-L-V2 supports Huawei Easy Operation, a solution that provides zero-touch deployment, replacement of faulty devices without additional configuration, USB-based deployment*, batch device configuration, and batch remote upgrade. The Easy Operation solution facilitates device deployment, upgrade, service provisioning, and other management and maintenance operations, and also greatly reduces O&M costs. CloudEngine S5735-L-V2 can be managed and maintained using Simple Network Management Protocol (SNMP) V1, V2, and V3, Command Line Interface (CLI), web-based network management system, or Secure Shell (SSH) V2.0. Additionally, it supports remote network monitoring (RMON), multiple log hosts, port traffic statistics collection, and network quality analysis, paving the way for network optimization and reconstruction.
- CloudEngine S5735-L-V2 supports MUX VLAN, which involves a principal VLAN and multiple subordinate VLANs. Subordinate VLANs are classified into group VLANs and separate VLANs. Ports in the principal VLAN can communicate with ports in subordinate VLANs. Ports in a subordinate group VLAN can communicate with each other, whereas ports in a subordinate separate VLAN cannot communicate with each other. CloudEngine S5735-L-V2 also supports VLAN-Based Spanning Tree (VBST) protocol.

Note: Only those switches with USB ports can USB-based deployment.

iStack

- CloudEngine S5735-L-V2 supports intelligent stack (iStack). This technology combines multiple switches into a logical switch. Member switches in a stack implement redundancy backup to improve device reliability and use inter-device link aggregation to improve link reliability.
- iStack provides high network scalability. You can increase ports, bandwidth, and processing capacity of a stack by simply adding member switches to the stack.
- iStack also simplifies device configuration and management. After a stack is set up, multiple physical switches are virtualized into one logical device. You can log in to any member switch in the stack to manage all the member switches in the stack. CloudEngine S5735-L-V2 support stacking through electrical ports.
- Some CloudEngine S5735-L-V2 supports two 12GE dedicated stack ports, which release uplink ports and do not need to be configured.

PoE Function

- **Perpetual PoE:** When a PoE switch is abnormal Power-off or the software version is upgraded, the power supply to PDs is not interrupted. This capability ensures that PDs are not powered off during the switch reboot.
- **Fast PoE:** PoE switches can supply power to PDs within seconds after they are powered on. This is different from common switches that generally take 1 to 3 minutes to start to supply power to PDs. When a PoE switch reboots due to a power failure, the PoE switch continues to supply power to the PDs immediately after being powered on without waiting until it finishes reboot. This greatly shortens the power failure time of PDs.

Network Slicing Functions

- CloudEngine S5735-L-V2 provides a range of VLAN slicing functions to meet diversified SLA requirements of different services and customers. Service isolation and bandwidth guarantee are implemented based on QoS. Slices can be completely isolated from each other without affecting each other. Traffic is isolated at the physical layer, and network slicing is performed for services on the same physical network. The Network Slicing technology can be used at the access, aggregation, and core layers to meet differentiated SLA requirements of new services on campus networks.

Intelligent O&M

- CloudEngine S5735-L-V2 provides telemetry technology to collect device data in real time and send the data to Huawei campus network analyzer CampusInsight. The CampusInsight analyzes network data based on the intelligent fault identification algorithm, accurately displays the real-time network status, effectively demarcates and locates faults in a timely manner, and identifies network problems that affect user experience, accurately guaranteeing user experience.

Intelligent Upgrade

- CloudEngine S5735-L-V2 supports the intelligent upgrade feature. Specifically, CloudEngine S5735-L-V2 obtains the version upgrade path and downloads the newest version for upgrade from the Huawei Online Upgrade Platform (HOUP). The entire upgrade process is highly automated and achieves one-click upgrade. In addition, preloading the version is supported, which greatly shortens the upgrade time and service interruption time.
- The intelligent upgrade feature greatly simplifies device upgrade operations and makes it possible for the customer to upgrade the version independently. This greatly reduces the customer's maintenance costs. In addition, the upgrade policies on the HOUP platform standardize the upgrade operations, which greatly reduces the risk of upgrade failures.

Cloud Management

- The Huawei cloud management platform allows users to configure, monitor, and inspect switches on the cloud, reducing on-site deployment and O&M manpower costs and decreasing network OPEX. Huawei switches support both cloud management and on-premise management modes. These two management modes can be flexibly switched as required to achieve smooth evolution while maximizing return on investment (ROI).

OPS

- CloudEngine S5735-L-V2 supports Open Programmability System (OPS), an open programmable system based on the Python language. IT administrators can program the O&M functions of a CloudEngine S5735-L-V2 switch through Python scripts to quickly innovate functions and implement intelligent O&M.

Licensing

CloudEngine S5735-L-V2 supports both the traditional feature-based licensing mode and the latest Huawei IDN One Software (N1 mode for short) licensing mode. The N1 mode is ideal for deploying Huawei CloudCampus Solution in the on-premises scenario, as it greatly enhances the customer experiences in purchasing and upgrading software services with simplicity.

Software Package Features in N1 Mode

| Switch Functions | N1 Basic Software | N1 Foundation Software Package | N1 Advanced Software Package |
|---|-------------------|--------------------------------|------------------------------|
| Basic network functions: Layer 2 functions, IPv4, IPv6 and others Note: For details, see the Service Features | √ | √ | √ |
| Basic network automation based on the iMaster NCE-Campus: <ul style="list-style-type: none"> Basic automation: Plug-and-play Basic monitoring: Application visualization NE management: Image and topology management and discovery User access authentication | × | √ | √ |
| Advanced network automation and intelligent O&M: CampusInsight basic functions | × | × | √ |

Product Specifications

Functions and Features

| Item | Description |
|--------------------------|---|
| MAC address table | MAC address learning and aging |
| | 32K MAC entries (MAX) |
| | Static, dynamic, and blackhole MAC address entries |
| | Packet filtering based on source MAC addresses |
| | Interface-based MAC learning limiting |
| VLAN features | 4K VLANs |
| | Voice VLAN |
| | MUX VLAN |
| | VLAN Stacking |
| Ethernet loop protection | Smart Link tree topology and Smart Link multi-instance, providing millisecond-level protection switchover |
| | ERPS (G.8032) |
| | STP (IEEE 802.1d), RSTP (IEEE 802.1w), and MSTP (IEEE 802.1s) |
| | BPDU protection, root protection, and loop protection |
| | BPDU tunnel |

| Item | Description |
|------------------------|---|
| | LLDP, LLDP-MED |
| Multicast | PIM DM, PIM SM, PIM SSM |
| | IGMPv1/v2/v3, IGMPv1/v2/v3 snooping, MLD snooping |
| | Multicast load balancing among member ports of a trunk |
| | Interface-based multicast traffic statistics |
| | Multicast VLAN |
| IP routing | Static route, RIP, RIPng, OSPF, OSPFv3, VRRP, VRRP6, Routing Policy, Policy-Based Routing |
| | Up to 4096 FIBv4 entries (MAX) |
| | Up to 1024 FIBv6 entries (MAX) |
| IPv6 features | Up to 1024 ND entries (MAX) |
| | Path MTU (PMTU) |
| | IPv6 ping, IPv6 tracer, and IPv6 Telnet |
| Reliability | LACP |
| | VRRP |
| | BFD |
| | LLDP |
| QoS/ACL | 2K rules per IPv4 ACL |
| | 2K rules per IPv6 ACL |
| | Rate limiting on packets sent and received by an interface |
| | Packet redirection |
| | Interface-based traffic policing and two-rate and three-color CAR |
| | Eight queues on each interface |
| | DRR, SP, and DRR+SP queue scheduling algorithms |
| | Re-marking of the 802.1p priority and DSCP priority |
| | Packet filtering at Layer 2 to Layer 4, filtering out invalid frames based on the source MAC address, destination MAC address, source IP address, destination IP address, TCP/UDP port number, protocol type, and VLAN ID |
| | Rate limiting in each queue and traffic shaping on interfaces |
| Network Slicing (VLAN) | |
| Security | Hierarchical user management and password protection |
| | DoS attack defense, ARP attack defense, and ICMP attack defense |
| | Binding of the IP address, MAC address, interface number, and VLAN ID |
| | Port isolation, port security, and sticky MAC |
| | Blackhole MAC address entries |
| | Limit on the number of learned MAC addresses |

| Item | Description |
|--------------------------------|---|
| | IEEE 802.1x authentication and limit on the number of users on an interface |
| | AAA authentication, RADIUS authentication, HWTACACS authentication, and NAC |
| | SSH V2.0 |
| | Hypertext Transfer Protocol Secure (HTTPS) |
| | CPU defense |
| | Blacklist and whitelist |
| | DHCP client, DHCP relay, DHCP server, DHCP snooping |
| | DHCPv6 client, DHCPv6 relay |
| Management and maintenance | iStack, stack bandwidth: 80Gbps |
| | Cloud management based on Netconf/Yang |
| | Virtual Cable Test (VCT) |
| | Remote configuration and maintenance using Telnet |
| | SNMPv1/v2/v3 |
| | RMON |
| | eSight and web-based NMS |
| | HTTPS |
| | LLDP/LLDP-MED |
| | System logs and multi-level alarms |
| | 802.3az EEE |
| | IFIT |
| | Port Mirroring |
| Registration Center Deployment | |
| Interoperability | Supports VBST (Compatible with PVST/PVST+/RPVST) |

Hardware Specifications

Hardware specifications of CloudEngine S5735-L8T4S-A-V2/L8P4S-A-V2/L10T4X-A-V2/L10T4X-TA-V2/ L8P2T4X-A-V2/L8P2T4X-TA-V2 models

| Item | | CloudEngine S5735-L8T4S-A-V2 | CloudEngine S5735-L8P4S-A-V2 | CloudEngine S5735-L10T4X-A-V2 CloudEngine S5735-L10T4X-TA-V2 | CloudEngine S5735-L8P2T4X-A-V2 CloudEngine S5735-L8P2T4X-TA-V2 |
|-------------------------|------------------------|------------------------------|------------------------------|---|---|
| Physical specifications | Dimensions (H x W x D) | 43.6 mm x 250 mm x 180 mm | 43.6 mm x 320 mm x 210 mm | 43.6 mm x 250 mm x 180 mm | 43.6 mm x 320 mm x 210 mm |
| | Chassis height | 1 U | 1 U | 1 U | 1 U |
| | Chassis weight | 2.22 kg | 3.05 kg | 2.22kg | 3.06kg |

| Item | | CloudEngine S5735-L8T4S-A-V2 | CloudEngine S5735-L8P4S-A-V2 | CloudEngine S5735-L10T4X-A-V2 CloudEngine S5735-L10T4X-TA-V2 | CloudEngine S5735-L8P2T4X-A-V2 CloudEngine S5735-L8P2T4X-TA-V2 |
|---|---|---|---|---|---|
| | (including packaging) | | | | |
| Fixed port | GE port | 8 | 8(PoE+) | 10 | 10 |
| | GE SFP port | 4 | 4 | NA | NA |
| | 10GE port | NA | NA | 4 | 4 |
| Management port | Console port (RJ45) | Supported | Supported | Supported | Supported |
| | USB Port | NA | NA | NA | NA |
| CPU | Frequency | 1.1 GHz | 1.1 GHz | 1.1 GHz | 1.1 GHz |
| | Core | 2 | 2 | 2 | 2 |
| Storage | Memory (DRAM) | 2 GB | 2 GB | 2 GB | 2 GB |
| Power supply system | Power supply type | Built-in AC | Built-in AC | Built-in AC | Built-in AC |
| | Rated voltage range | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz |
| | Maximum voltage range | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz |
| | Maximum input current | 0.8 A | 3 A | 0.8A | 3A |
| | Maximum power consumption of the device | 21.52 W | <ul style="list-style-type: none"> 25.09 W (without PD) 166.65 W (with PD, PD power consumption of 125 W) | 29.54 W | <ul style="list-style-type: none"> 32.33 W (without PD) 151.85 W (with PD, PD power consumption of 125 W) |
| | Power consumption in the case of 30% traffic load ¹ | 15.95 W | 19.99 W | 19.24 W | 23.33 W |
| | Power consumption in the case of 100% traffic load ¹ | 18.71 W | 19.99 W | 22.63 W | 23.77 W |
| Power consumption in the case of 0% traffic load ¹ | 13.02 W | 17.19 W | 15.1 W | 16.75 W | |
| Heat dissipation system | Heat dissipation mode | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment |
| | Number of fan | 1 | 1 | 1 | 1 |

| Item | | CloudEngine S5735-L8T4S-A-V2 | CloudEngine S5735-L8P4S-A-V2 | CloudEngine S5735-L10T4X-A-V2 CloudEngine S5735-L10T4X-TA-V2 | CloudEngine S5735-L8P2T4X-A-V2 CloudEngine S5735-L8P2T4X-TA-V2 |
|---|---|--|--|--|--|
| | modules | | | | |
| | Airflow | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right |
| | Maximum heat dissipation of the device (BTU/hour) | 81.96 | <ul style="list-style-type: none"> Without PDs: 94.14 With PDs: 590.81 | 71.82 | <ul style="list-style-type: none"> Without PDs: 85.98 With PDs: 523.15 |
| Environment parameters | Long-term operating temperature | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. |
| | Short-term operating temperature | NA | NA | NA | NA |
| | Storage temperature | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| | Relative humidity | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) |
| | Operating altitude | 5000 m | 5000 m | 5000 m | 5000 m |
| | Noise under normal temperature (sound power) | 44.5 dB(A) | 47 dB(A) | 44.5 dB(A) | 47 dB(A) |
| | Noise under high temperature (sound power) | 53 dB(A) | 57.3 dB(A) | 53 dB(A) | 57.3 dB(A) |
| | Noise under normal temperature (sound pressure) | 32.5 dB(A) | 35 dB(A) | 32.5 dB(A) | 35 dB(A) |
| | Surge protection specification (RJ45 service port) | ±7 kV in common mode | ±7 kV in common mode | ±7 kV in common mode | ±7 kV in common mode |
| Surge protection specification (power port) | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common | |

| Item | | CloudEngine S5735-L8T4S-A-V2 | CloudEngine S5735-L8P4S-A-V2 | CloudEngine S5735-L10T4X-A-V2 CloudEngine S5735-L10T4X-TA-V2 | CloudEngine S5735-L8P2T4X-A-V2 CloudEngine S5735-L8P2T4X-TA-V2 |
|---------------|--------------|--|--|--|--|
| | | mode: ± 6 kV | mode: ± 6 kV | mode: ± 6 kV | mode: ± 6 kV |
| Reliability | MTBF (year) | 75.32 | 69.71 | 73.83/72.49 | 68.4/67.25 |
| | MTTR (hour) | 2 | 2 | 2 | 2 |
| | Availability | > 0.99999 | > 0.99999 | > 0.99999 | > 0.99999 |
| Certification | | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification |

Hardware specifications of CloudEngine S5735-L16T4S-A-V2/L24T4S-A-V2/L24P4S-A-V2/ L24T4XE-A-V2 models

| Item | | CloudEngine S5735-L16T4S-A-V2 | CloudEngine S5735-L24T4S-A-V2 | CloudEngine S5735-L24P4S-A-V2 | CloudEngine S5735-L24T4XE-A-V2 |
|-------------------------|--------------------------------------|--|---|---|---|
| Physical specifications | Dimensions (H x W x D) | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm |
| | Chassis height | 1 U | 1U | 1 U | 1 U |
| | Chassis weight (including packaging) | 3.34kg | 3.44 kg | 3.79 kg | 3.46 kg |
| Fixed port | GE port | 16 | 24 | 24(PoE+) | 24 |
| | GE SFP port | 4 | 4 | 4 | NA |
| | 10GE port | NA | NA | NA | 4 |
| Management port | Console port (RJ45) | Supported | Supported | Supported | Supported |
| | USB Port | NA | NA | NA | Supported |
| CPU | Frequency | 1.1 GHz | NA | NA | USB 2.0 |
| | Core | 2 | 1.1 GHz | 1.1 GHz | 1.1 GHz |
| Storage | Memory (DRAM) | 2 GB | 2 GB | 2 GB | 2 GB |
| Power supply system | Power supply type | Built-in AC | Built-in AC | Built-in AC | Built-in AC |
| | Rated voltage range | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz | AC input: 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz |
| | Maximum voltage range | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 | <ul style="list-style-type: none"> AC input: 90 V AC to 264 V AC, 47 Hz to |

| Item | | CloudEngine S5735-L16T4S-A-V2 | CloudEngine S5735-L24T4S-A-V2 | CloudEngine S5735-L24P4S-A-V2 | CloudEngine S5735-L24T4XE-A-V2 |
|-------------------------|---|--|--|--|--|
| | | 45 Hz to 65 Hz | 65 Hz | Hz to 65 Hz | 63 Hz |
| | Maximum input current | 0.8A | 0.8A | 6A | 0.8A |
| | Maximum power consumption of the device | 28.84 W | 33.04 W | <ul style="list-style-type: none"> 43.35 W (without PD) 484.91 W (with PD, PD Power consumption of :400W) | 37.03 W |
| | Power consumption in the case of 30% traffic load ¹ | 21.17 W | 26.37 W | 36.32 W | 28.48 W |
| | Power consumption in the case of 100% traffic load ¹ | 24.35 W | 27.05 W | 36.79 W | 29.36 W |
| | Power consumption in the case of 0% traffic load ¹ | 16.30 W | 19.00 W | 27.07 W | 17.53 W |
| Heat dissipation system | Heat dissipation mode | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment |
| | Number of fan modules | 1 | 1 | 2 | 1 |
| | Airflow | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right |
| | Maximum heat dissipation of the device (BTU/hour) | 103.73 | 113.96 | <ul style="list-style-type: none"> Without PDs: 148.77 With PDs: 1667.15 | 120.79 |
| Environment parameters | Long-term operating temperature | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. |

| Item | | CloudEngine S5735-L16T4S-A-V2 | CloudEngine S5735-L24T4S-A-V2 | CloudEngine S5735-L24P4S-A-V2 | CloudEngine S5735-L24T4XE-A-V2 |
|---------------|--|--|--|--|--|
| | Short-term operating temperature | NA | NA | NA | NA |
| | Storage temperature | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| | Relative humidity | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) |
| | Operating altitude | 5000 m | 5000 m | 5000 m | 5000 m |
| | Noise under normal temperature (sound power) | 47 dB(A) | 47 dB(A) | 49.3 dB(A) | 47 dB(A) |
| | Noise under high temperature (sound power) | 51 dB(A) | 51 dB(A) | 63 dB(A) | 51 dB(A) |
| | Noise under normal temperature (sound pressure) | 35 dB(A) | 35 dB(A) | 37.3 dB(A) | 35 dB(A) |
| | Surge protection specification (RJ45 service port) | ±7 kV in common mode | ±7 kV in common mode | ±7 kV in common mode | ±7 kV in common mode |
| | Surge protection specification (power port) | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ± 6 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ± 6 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ± 6 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ± 6 kV |
| Reliability | MTBF (year) | 72.43 | 70.75 | 60.18 | 68.7 |
| | MTTR (hour) | 2 | 2 | 2 | 2 |
| | Availability | > 0.99999 | > 0.99999 | > 0.99999 | > 0.99999 |
| Certification | | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification |

Hardware specifications of CloudEngine S5735-L24T4XE-D-V2/-L24P4XE-A-V2/-L24P4XE-TA-V2/-L48T4S-A-V2/-L48LP4S-A-V2 models

| Item | | CloudEngine S5735-L24T4XE-D-V2 | CloudEngine S5735-L24P4XE-A-V2 CloudEngine S5735-L24P4XE-TA-V2 | CloudEngine S5735-L48T4S-A-V2 | CloudEngine S5735-L48LP4S-A-V2 |
|-------------------------|--|--------------------------------|--|---|---|
| Physical specifications | Dimensions (H x W x D) | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm |
| | Chassis height | 1 U | 1 U | 1 U | 1 U |
| | Chassis weight (including packaging) | 3.44 kg | 3.81 kg | 3.59 kg | 4.29 kg |
| Fixed port | GE Base-T port | 24 | 24(PoE+) | 48 | 48(PoE+) |
| | GE SFP port | NA | NA | 4 | 4 |
| | 10GE port | 4 | 4 | NA | NA |
| | Dedicated 12GE stack port | 2 | 2 | NA | NA |
| Management port | Console port (RJ45) | Supported | Supported | Supported | Supported |
| | USB port | Supported | Supported | NA | NA |
| CPU | Frequency | 1.1 GHz | 1.1 GHz | 1.1 GHz | 1.1 GHz |
| | Core | 2 | 2 | 2 | 2 |
| Storage | Memory (DRAM) | 2 GB | 2 GB | 2 GB | 2 GB |
| Power supply system | Power supply type | Built-in DC power | Built-in AC power | Built-in AC power | Built-in AC power |
| | Rated voltage range | -48V DC~-60V DC | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz |
| | Maximum voltage range | -38.4V DC~-72V DC | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz |
| | Maximum input current | 6 A | 6 A | 1.6 A | 6 A |
| | Maximum power consumption of the device | 36.33 W | <ul style="list-style-type: none"> 55.4 W (without PD) 496.08 W(with PD,PD Power consumption of :400W) | 43.3 W | <ul style="list-style-type: none"> 62.7 W (without PD) 462.8 W(with PD,PD Power consumption of :380W) |
| | Power consumption in the case of 30% traffic load ¹ | 30.61 W | 39.84 W | 36.15 W | 48.64 W |
| | Power consumption in the case of 100% | 35.92 W | 40.42 W | 36.91 W | 48.68 W |

| Item | | CloudEngine S5735-L24T4XE-D-V2 | CloudEngine S5735-L24P4XE-A-V2 CloudEngine S5735-L24P4XE-TA-V2 | CloudEngine S5735-L48T4S-A-V2 | CloudEngine S5735-L48LP4S-A-V2 |
|-------------------------|---|--|--|--|--|
| | traffic load ¹ | | | | |
| | Power consumption in the case of 0% traffic load ¹ | 25.81 W | 29.17 W | 18.8 W | 34.04 W |
| Heat dissipation system | Heat dissipation mode | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment |
| | Number of fan modules | 1 | 2 | 1 | 2 |
| | Airflow | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right | Air intake from left and front, air exhaustion from right |
| | Maximum heat dissipation of the device (BTU/hour) | 120.79 | without PD :186.3 with PD: 1684.21 | 146.72 | without PD :179.07 with PD: 1619.72 |
| Environment parameters | Long-term operating temperature | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +45°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to +50°C 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. |
| | Short-term operating temperature | NA | NA | NA | NA |
| | Storage temperature | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| | Relative humidity | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) |
| | Operating altitude | 5000 m | 5000 m | 5000 m | 5000 m |
| | Noise under normal temperature (sound power) | 47 dB(A) | 49.3 dB(A) | 46.6 dB(A) | 49.3 dB(A) |
| | Noise under high temperature (sound power) | 51 dB(A) | 63 dB(A) | 54.3 dB(A) | 63 dB(A) |
| | Noise under normal | 35 dB(A) | 37.3 dB(A) | 34.6 dB(A) | 37.3 dB(A) |

| Item | | CloudEngine S5735-L24T4XE-D-V2 | CloudEngine S5735-L24P4XE-A-V2 CloudEngine S5735-L24P4XE-TA-V2 | CloudEngine S5735-L48T4S-A-V2 | CloudEngine S5735-L48LP4S-A-V2 |
|---------------|--|--|--|--|--|
| | temperature (sound pressure) | | | | |
| | Surge protection specification (RJ45 service port) | ±7 kV in common mode | ±7 kV in common mode | ±7 kV in common mode | ±4 kV in common mode |
| | Surge protection specification (power port) | <ul style="list-style-type: none"> Differential mode: ± 2 kV Common mode: ±4 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ± 6 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ±6 kV | <ul style="list-style-type: none"> Differential mode: ± 6 kV Common mode: ±6 kV |
| Reliability | MTBF (year) | 68.7 | 59.13/58.27 | 40.61 | 48.14 |
| | MTTR (hour) | 2 | 2 | 2 | 2 |
| | Availability | > 0.99999 | > 0.99999 | > 0.99999 | > 0.99999 |
| Certification | | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification | <ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification |

Hardware specifications of CloudEngine S5735-L48T4XE-A-V2/L48T4XE-TA-V2/S5735-L48T4XE-D-V2/L48P4XE-A-V2/L48LP4XE-A-V2 models

| Item | | CloudEngine S5735-L48T4XE-A-V2 CloudEngine S5735-L48T4XE-TA-V2 | CloudEngine S5735-L48T4XE-D-V2 | CloudEngine S5735-L48P4XE-A-V2 | CloudEngine S5735-L48LP4XE-A-V2 |
|-------------------------|--------------------------------------|---|--------------------------------|--------------------------------|---------------------------------|
| Physical specifications | Dimensions (H x W x D) | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 220 mm | 43.6 mm x 442 mm x 420 mm | 43.6 mm x 442 mm x 220 mm |
| | Chassis height | 1 U | 1 U | 1 U | 1 U |
| | Chassis weight (including packaging) | 3.62 kg | 3.6 kg | 8.9 kg | 4.32 kg |
| Fixed port | GE Base-T port | 48 | 48 | 48(PoE+) | 48(PoE+) |
| | GE SFP port | NA | NA | NA | NA |
| | 10GE port | 4 | 4 | 4 | 4 |
| | Dedicated 12GE stack port | 2 | 2 | 2 | 2 |
| Management port | Console port (RJ45) | Supported | Supported | Supported | Supported |

| Item | | CloudEngine S5735-L48T4XE-A-V2 CloudEngine S5735-L48T4XE-TA-V2 | CloudEngine S5735-L48T4XE-D-V2 | CloudEngine S5735-L48P4XE-A-V2 | CloudEngine S5735-L48LP4XE-A-V2 |
|-------------------------|---|---|--|---|--|
| | USB port | Supported | Supported | Supported | Supported |
| CPU | Frequency | 1.1 GHz | 1.1 GHz | 1.1 GHz | 1.1 GHz |
| | Core | 2 | 2 | 2 | 2 |
| Storage | Memory (DRAM) | 2 GB | 2 GB | 2 GB | 2 GB |
| Power supply system | Power supply type | Built-in AC | Built-in DC | Built-in AC | Built-in AC |
| | Rated voltage range | 100 V AC to 240 V AC, 50/60 Hz | -48V DC~-60V DC | 100 V AC to 240 V AC, 50/60 Hz | 100 V AC to 240 V AC, 50/60 Hz |
| | Maximum voltage range | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | -38.4V DC~-72V DC | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz | <ul style="list-style-type: none"> AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz |
| | Maximum input current | 1.6 A | 6 A | Depending on power module | 6 A |
| | Maximum power consumption of the device | 49.48 W | 48.42 W | <ul style="list-style-type: none"> 76.66 W (without PD) 993.74 W(with PD,PD Power consumption of :846 W) | <ul style="list-style-type: none"> 65.7 W (without PD) 464.8 W(with PD,PD Power consumption of :380W) |
| | Power consumption in the case of 30% traffic load ¹ | 41.06 W | 40.29 W | 54.78 W | 49.81 W |
| | Power consumption in the case of 100% traffic load ¹ | 43.73 W | 41.57 W | 55.9 W | 50.14 W |
| | Power consumption in the case of 0% traffic load ¹ | 19.68 W | 23.52 W | 36.75 W | 32.09 W |
| Heat dissipation system | Heat dissipation mode | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment | Air-cooled heat dissipation and intelligent speed adjustment |
| | Number of fan modules | 1 | 1 | 2 | 2 |
| | Airflow | Air intake from left and air exhaust from right | Air intake from left and air exhaust from right | Air intake from left and air exhaust from right | Air intake from left and air exhaust from right |
| | Maximum heat dissipation of the device (BTU/hour) | 170.61 | 163.78 | without PD :286.62 with PD: 3473.52 | without PD :189.3 with PD: 1629.96 |
| Environment | Long-term operating | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to | <ul style="list-style-type: none"> 0-1800 m altitude: -5°C to |

| Item | | CloudEngine S5735-L48T4XE-A-V2 CloudEngine S5735-L48T4XE-TA-V2 | CloudEngine S5735-L48T4XE-D-V2 | CloudEngine S5735-L48P4XE-A-V2 | CloudEngine S5735-L48LP4XE-A-V2 |
|---------------|--|---|---|---|---|
| parameters | temperature | +50°C • 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | +50°C • 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | +50°C • 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. | +50°C • 1800-5000 m altitude: The operating temperature reduces by 1°C every time the altitude increases by 220 m. |
| | Short-term operating temperature | NA | NA | NA | NA |
| | Storage temperature | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| | Relative humidity | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) | 5%-95%(non-condensing) |
| | Operating altitude | 5000 m | 5000 m | 5000 m | 5000 m |
| | Noise under normal temperature (sound power) | 46.6 dB(A) | 46.6 dB(A) | 49.3 dB(A) | 49.3 dB(A) |
| | Noise under high temperature (sound power) | 54.3 dB(A) | 54.3 dB(A) | 63 dB(A) | 63 dB(A) |
| | Noise under normal temperature (sound pressure) | 34.6 dB(A) | 34.6 dB(A) | 37.3 dB(A) | 37.3 dB(A) |
| | Surge protection specification (RJ45 service port) | ±7 kV in common mode | ±7 kV in common mode | ±6 kV in common mode | ±6 kV in common mode |
| | Surge protection specification (power port) | • Differential mode: ± 6 kV • Common mode: ±6 kV | • Differential mode: ± 2 kV • Common mode: ±4 kV | • Differential mode: ± 6 kV • Common mode: ±6 kV | • Differential mode: ± 6 kV • Common mode: ±6 kV |
| Reliability | MTBF (year) | 40.01/39.62 | 61.67 | 46.89 | 47.31 |
| | MTTR (hour) | 2 | 2 | 2 | 2 |
| | Availability | > 0.99999 | > 0.99999 | > 0.99999 | > 0.99999 |
| Certification | | • EMC certification • Safety certification • Manufacturing certification | • EMC certification • Safety certification • Manufacturing certification | • EMC certification • Safety certification • Manufacturing certification | • EMC certification • Safety certification • Manufacturing certification |

NOTE


1: The Typical power consumption is calculated under 30% service traffic load conditions according to the ATIS standard. Additionally, the EEE function is enabled and there is no PoE power output.

The Static power consumption is calculated under 0% service traffic load conditions according to the ATIS standard. Additionally, the EEE function is enabled and there is no PoE power output.

Networking and Applications

Medium or Large-Scale Enterprise Campus Network

CloudEngine S5735-L-V2 series switches can be deployed at the access layer of a campus network to build a high-performance and highly reliable enterprise network.



Safety and Regulatory Compliance

Safety and regulatory compliance of the CloudEngine S5735-L series

| Certification Category | Description |
|------------------------|-------------|
|------------------------|-------------|

| Certification Category | Description |
|-------------------------------------|---|
| Safety | <ul style="list-style-type: none"> • IEC 60950-1 • EN 60950-1/A11/A12 • UL 60950-1 • CSA C22.2 No 60950-1 • AS/NZS 60950.1 • CNS 14336-1 |
| Laser safety | <ul style="list-style-type: none"> • IEC60825-1 • IEC60825-2 • EN60825-1 • EN60825-2 |
| Electromagnetic Compatibility (EMC) | <ul style="list-style-type: none"> • CISPR22 Class A • CISPR24 • EN55022 Class A • EN55024 • ETSI EN 300 386 Class A • CFR 47 FCC Part 15 Class A • ICES 003 Class A • AS/NZS CISPR22 Class A • VCCI Class A • EN61000-3-2 • EN61000-3-3 • IEC61000-4-2 • ITU-T K 20 • ITU-T K 21 • ITU-T K 44 • CNS13438 |
| Environment | <ul style="list-style-type: none"> • RoHS • REACH • WEEE |

NOTE

- EMC: electromagnetic compatibility
- CISPR: International Special Committee on Radio Interference
- EN: European Standard
- ETSI: European Telecommunications Standards Institute
- CFR: Code of Federal Regulations
- FCC: Federal Communication Commission
- IEC: International Electrotechnical Commission
- AS/NZS: Australian/New Zealand Standard
- VCCI: Voluntary Control Council for Interference
- UL: Underwriters Laboratories
- CSA: Canadian Standards Association
- IEEE: Institute of Electrical and Electronics Engineers
- RoHS: restriction of the use of certain hazardous substances

- REACH: Registration Evaluation Authorization and Restriction of Chemicals
- WEEE: Waste Electrical and Electronic Equipment

MIB and Standards Compliance

Supported MIBs

Supported MIBs by the CloudEngine S5735-L-V2 series

| Category | MIB |
|------------------------|--|
| Public MIB | <ul style="list-style-type: none"> • BRIDGE-MIB • DISMAN-NSLOOKUP-MIB • DISMAN-PING-MIB • DISMAN-TRACEROUTE-MIB • ENTITY-MIB • EtherLike-MIB • IF-MIB • IP-FORWARD-MIB • IPv6-MIB • LAG-MIB • LLDP-EXT-DOT1-MIB • LLDP-EXT-DOT3-MIB • LLDP-MIB • NOTIFICATION-LOG-MIB • NQA-MIB • P-BRIDGE-MIB • Q-BRIDGE-MIB • RFC1213-MIB • RMON-MIB • SAVI-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMPv2-MIB • SNMP-VIEW-BASED-ACM-MIB • TCP-MIB • UDP-MIB |
| Huawei-proprietary MIB | <ul style="list-style-type: none"> • HUAWEI-AAA-MIB • HUAWEI-ACL-MIB • HUAWEI-ALARM-MIB • HUAWEI-ALARM-RELIABILITY-MIB • HUAWEI-BASE-TRAP-MIB • HUAWEI-BRAS-RADIUS-MIB • HUAWEI-BRAS-SRVCFG-EAP-MIB |

| Category | MIB |
|----------|---|
| | <ul style="list-style-type: none"> • HUAWEI-BRAS-SRVCFG-STATICUSER-MIB • HUAWEI-CBQOS-MIB • HUAWEI-CDP-COMPLIANCE-MIB • HUAWEI-CONFIG-MAN-MIB • HUAWEI-CPU-MIB • HUAWEI-DAD-TRAP-MIB • HUAWEI-DATASYNC-MIB • HUAWEI-DEVICE-MIB • HUAWEI-DHCPR-MIB • HUAWEI-DHCPS-MIB • HUAWEI-DHCP-SNOOPING-MIB • HUAWEI-DIE-MIB • HUAWEI-DNS-MIB • HUAWEI-DLDP-MIB • HUAWEI-ERPS-MIB • HUAWEI-ERRORDOWN-MIB • HUAWEI-ENERGYMNGT-MIB • HUAWEI-EASY-OPERATION-MIB • HUAWEI-ENTITY-EXTENT-MIB • HUAWEI-ENTITY-TRAP-MIB • HUAWEI-ETHARP-MIB • HUAWEI-ETHOAM-MIB • HUAWEI-FLASH-MAN-MIB • HUAWEI-FWD-RES-TRAP-MIB • HUAWEI-GARP-APP-MIB • HUAWEI-GTL-MIB • HUAWEI-HGMP-MIB • HUAWEI-HWTACACS-MIB • HUAWEI-IF-EXT-MIB • HUAWEI-INFOCENTER-MIB • HUAWEI-IPPOOL-MIB • HUAWEI-IPV6-MIB • HUAWEI-ISOLATE-MIB • HUAWEI-L2IF-MIB • HUAWEI-L2MAM-MIB • HUAWEI-L2VLAN-MIB • HUAWEI_LDT-MIB • HUAWEI-LLDP-MIB • HUAWEI-MAC-AUTHEN-MIB • HUAWEI-MEMORY-MIB • HUAWEI-MFF-MIB • HUAWEI-MFLP-MIB • HUAWEI-MSTP-MIB • HUAWEI-MULTICAST-MIB • HUAWEI-NTPV3-MIB |

| Category | MIB |
|----------|--|
| | <ul style="list-style-type: none"> • HUAWEI-PERFORMANCE-MIB • HUAWEI-PERFMGMT-MIB • HUAWEI-PORT-MIB • HUAWEI-PORTAL-MIB • HUAWEI-QINQ-MIB • HUAWEI-RM-EXT-MIB • HUAWEI-RRPP-MIB • HUAWEI-SECURITY-MIB • HUAWEI-SEP-MIB • HUAWEI-SNMP-EXT-MIB • HUAWEI-SSH-MIB • HUAWEI-STACK-MIB • HUAWEI-SWITCH-L2MAM-EXT-MIB • HUAWEI-SWITCH-SRV-TRAP-MIB • HUAWEI-SYS-MAN-MIB • HUAWEI-TCP-MIB • HUAWEI-TFTPC-MIB • HUAWEI-TRNG-MIB • HUAWEI-UNIMNG-MIB • HUAWEI-USA-MIB • HUAWEI-XQOS-MIB |

NOTE

For more detailed information of MIBs supported by the CloudEngine S5735-L-V2 series, visit <https://support.huawei.com/enterprise/en/switches/s5700-pid-6691579?category=reference-guides&subcategory=mib-reference>.

Standard Compliance

Standard compliance list of the CloudEngine S5735-L-V2 series

| Standard Organization | Standard or Protocol |
|-----------------------|--|
| IETF | <ul style="list-style-type: none"> • RFC 768 User Datagram Protocol (UDP) • RFC 792 Internet Control Message Protocol (ICMP) • RFC 793 Transmission Control Protocol (TCP) • RFC 826 Ethernet Address Resolution Protocol (ARP) • RFC 854 Telnet Protocol Specification • RFC 951 Bootstrap Protocol (BOOTP) • RFC 959 File Transfer Protocol (FTP) • RFC 1058 Routing Information Protocol (RIP) • RFC 1112 Host extensions for IP multicasting • RFC 1157 A Simple Network Management Protocol (SNMP) • RFC 1256 ICMP Router Discovery • RFC 1305 Network Time Protocol Version 3 (NTP) • RFC 1349 Internet Protocol (IP) • RFC 1493 Definitions of Managed Objects for Bridges • RFC 1542 Clarifications and Extensions for the Bootstrap Protocol |

| Standard Organization | Standard or Protocol |
|-----------------------|---|
| | <ul style="list-style-type: none"> • RFC 1643 Ethernet Interface MIB • RFC 1757 Remote Network Monitoring (RMON) • RFC 1901 Introduction to Community-based SNMPv2 • RFC 1902-1907 SNMP v2 • RFC 1981 Path MTU Discovery for IP version 6 • RFC 2131 Dynamic Host Configuration Protocol (DHCP) • RFC 2460 Internet Protocol, Version 6 Specification (IPv6) • RFC 2461 Neighbor Discovery for IP Version 6 (IPv6) • RFC 2462 IPv6 Stateless Address Auto configuration • RFC 2463 Internet Control Message Protocol for IPv6 (ICMPv6) • RFC 2474 Differentiated Services Field (DS Field) • RFC 2863 The Interfaces Group MIB • RFC 2597 Assured Forwarding PHB Group • RFC 2598 An Expedited Forwarding PHB • RFC 2571 SNMP Management Frameworks • RFC 2865 Remote Authentication Dial In User Service (RADIUS) • RFC 3046 DHCP Option82 • RFC 3513 IP Version 6 Addressing Architecture • RFC 3579 RADIUS Support For EAP • draft-grant-tacacs-02 TACACS+ • RFC 6241 Network Configuration Protocol (NETCONF) • RFC 6020 YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF) |
| IEEE | <ul style="list-style-type: none"> • IEEE 802.1D Media Access Control (MAC) Bridges • IEEE 802.1p Traffic Class Expediting and Dynamic Multicast Filtering • IEEE 802.1Q Virtual Bridged Local Area Networks • IEEE 802.1ad Provider Bridges • IEEE 802.2 Logical Link Control • IEEE Std 802.3 CSMA/CD • IEEE Std 802.3ab 1000BASE-T specification • IEEE Std 802.3ad Aggregation of Multiple Link Segments • IEEE Std 802.3ae 10GE WEN/LAN Standard • IEEE Std 802.3x Full Duplex and flow control • IEEE Std 802.3z Gigabit Ethernet Standard • IEEE802.1ax/IEEE802.3ad Link Aggregation • IEEE 802.1ab Link Layer Discovery Protocol • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1w Rapid Spanning Tree Protocol • IEEE 802.1s Multiple Spanning Tree Protocol • IEEE 802.1x Port based network access control protocol • IEEE 802.3af DTE Power via MIDI • IEEE 802.3at DTE Power via the MDI Enhancements • IEEE 802.3az Energy Efficient Ethernet |

| Standard Organization | Standard or Protocol |
|-----------------------|---|
| ITU | <ul style="list-style-type: none"> • ITU SG13 Y.17ethoam • ITU SG13 QoS control Ethernet-Based IP Access • ITU-T Y.1731 ETH OAM performance monitor |
| MEF | <ul style="list-style-type: none"> • MEF 2 Requirements and Framework for Ethernet Service Protection • MEF 9 Abstract Test Suite for Ethernet Services at the UNI • MEF 11 UNI Requirements and Framework • MEF 15 Requirements for Management of Metro Ethernet Phase 1 Network Elements • MEF 17 Service OAM Framework and Requirements • MEF 20 UNI Type 2 Implementation Agreement • MEF 23 Class of Service Phase 1 Implementation Agreement • XMODEM/YMODEM Protocol Reference |

NOTE

The listed standards and protocols are fully or partially supported by Huawei switches. For details, visit <http://e.huawei.com/en> or contact your local Huawei sales office.

Ordering Information

| Model | Product Description |
|---------------------------------|--|
| CloudEngine S5735-L8T4S-A-V2 | CloudEngine S5735-L8T4S-A-V2 (8*10/100/1000BASE-T ports, 4*GE SFP ports, AC power) |
| CloudEngine S5735-L8P4S-A-V2 | CloudEngine S5735-L8P4S-A-V2 (8*10/100/1000BASE-T ports, 4*GE SFP ports, PoE+, AC power) |
| CloudEngine S5735-L10T4X-A-V2 | CloudEngine S5735-L10T4X-TA-V2 (10*10/100/1000BASE-T ports, 4*10GE SFP+ ports, AC power) |
| CloudEngine S5735-L10T4X-TA-V2 | CloudEngine S5735-L10T4X-TA-V2 (10*10/100/1000BASE-T ports, 4*10GE SFP+ ports, HTM, AC power) |
| CloudEngine S5735-L8P2T4X-A-V2 | CloudEngine S5735-L8P2T4X-A-V2 (8*10/100/1000BASE-T ports(PoE+), 2*10/100/1000BASE-T ports, 4*10GE SFP+ ports, AC power) |
| CloudEngine S5735-L8P2T4X-TA-V2 | CloudEngine S5735-L8P2T4X-TA-V2 (8*10/100/1000BASE-T ports(PoE+), 2*10/100/1000BASE-T ports, 4*10GE SFP+ ports, HTM, AC power) |
| CloudEngine S5735-L16T4S-A-V2 | CloudEngine S5735-L16T4S-A-V2 (16*10/100/1000BASE-T ports, 4*GE SFP ports, AC power) |
| CloudEngine S5735-L24T4S-A-V2 | CloudEngine S5735-L24T4S-A-V2 (24*10/100/1000BASE-T ports, 4*GE SFP ports, AC power) |
| CloudEngine S5735-L24P4S-A-V2 | CloudEngine S5735-L24P4S-A-V2 (24*10/100/1000BASE-T ports, 4*GE SFP ports, PoE+, AC power) |
| CloudEngine S5735-L24T4XE-A-V2 | CloudEngine S5735-L24T4XE-A-V2 (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, AC power) |
| CloudEngine S5735-L24T4XE-D-V2 | CloudEngine S5735-L24T4XE-D-V2 (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, DC power) |
| CloudEngine S5735- | CloudEngine S5735-L24P4XE-A-V2 (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports, |

| Model | Product Description |
|---------------------------------|---|
| L24P4XE-A-V2 | 2*stack ports, PoE+, AC power) |
| CloudEngine S5735-L24P4XE-TA-V2 | CloudEngine S5735-L24P4XE-TA-V2 (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, PoE+, HTM, AC power) |
| CloudEngine S5735-L48T4S-A-V2 | CloudEngine S5735-L48T4S-A-V2 (48*10/100/1000BASE-T ports, 4*GE SFP ports, AC power) |
| CloudEngine S5735-L48LP4S-A-V2 | CloudEngine S5735-L48LP4S-A-V2 (48*10/100/1000BASE-T ports, 4*GE SFP ports, PoE+, AC power) |
| CloudEngine S5735-L48T4XE-TA-V2 | CloudEngine S5735-L48T4XE-TA-V2 (48*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, PoE+, HTM, AC power) |
| CloudEngine S5735-L48T4XE-D-V2 | CloudEngine S5735-L48T4XE-D-V2 (48*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, PoE+, PoE+, DC power) |
| CloudEngine S5735-L48P4XE-A-V2 | CloudEngine S5735-L48P4XE-A-V2 (48*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, PoE+, AC power) |
| CloudEngine S5735-L48LP4XE-A-V2 | CloudEngine S5735-L48LP4XE-A-V2 (48*10/100/1000BASE-T ports, 4*10GE SFP+ ports, 2*stack ports, PoE+, 1*AC power) |
| PAC1000S56-EB | 1000W AC PoE power module, can be used in CloudEngine S5735-L48P4XE-A-V2 |
| PAC1000S56-DB | 1000W AC PoE power module, can be used in CloudEngine S5735-L48P4X-A |
| N1-S57L-M-Lic | S57XX-L Series Basic SW,Per Device |
| N1-S57L-M-SnS1Y | S57XX-L Series Basic SW,SnS,Per Device,1Year |
| N1-S57L-F-Lic | N1-CloudCampus,Foundation,S57XX-L Series,Per Device |
| N1-S57L-F-SnS | N1-CloudCampus,Foundation,S57XX-L Series,SnS,Per Device |
| N1-S57L-A-Lic | N1-CloudCampus,Advanced,S57XX-L Series,Per Device |
| N1-S57L-A-SnS | N1-CloudCampus,Advanced,S57XX-L Series,SnS,Per Device |
| N1-S57L-FToA-Lic | N1-Upgrade-Foundation to Advanced,S57XX-L,Per Device |
| N1-S57L-FToA-SnS | N1-Upgrade-Foundation to Advanced,S57XX-L,SnS,Per Device |

More Information


For more information about Huawei Campus Switches, visit <http://e.huawei.com> or contact us in the following ways:

- Global service hotline: <http://e.huawei.com/en/service-hotline>
- Logging in to the Huawei Enterprise technical support website: <http://support.huawei.com/enterprise/>
- Sending an email to the customer service mailbox: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website:e.huawei.com